

Gallery:





Screenshot





Features:

- **Pill Counting**
- [Fast Counting with Direct Vial Filling](#)
- [DRX System software preinstalled on an embedded Network / WiFi computer](#)
- [Interactive Administrative panel access through any PC web browser on the network](#)
- [Counting Transaction Reports and Data Exporting](#)
- [Automatic E-mail Reporting](#)
- [Instant E-mail Alerts for user caused miscounts and failed Rx Verifications](#)
- [Preloaded NDC directory database with Drug Name and Drug Details displayed](#)
- [Versatile connection capabilities - remote via the internet, Wi-Fi, or local network](#)
- [Miscounted Transaction and Failed Rx Verification Reports](#)
- [Most Frequently Counted prescriptions reports](#)
- [Rx NDC Verification](#)
- [APA - Advanced Pill Counting Accuracy](#)
- [Automatic NDC Updating with Advanced Pill Counting Accuracy \(APA\)](#)
- [Quick user Barcode login](#)
- [Prescription Size Entry](#)
- [Onscreen Instructions](#)
- [Omni-directional Laser Barcode Scanner](#)
- [LOT Number Labeling](#)
- [Counting Transaction Printing](#)

- [Full server management for custom network requirements](#)
- [NTEP Certified and Legal for trade](#)

- **Compounding**
 - Filling Meter
 - Remaining to Fill
 - Ingredient Labeling
 - Recipe Archiving
 - Recipe Printing
 - Onscreen Instructions

- **Other Features**
 - Auto Calibration
 - Graphical Display
 - Sealed Keypad
 - Navigation Keys
 - Dual TARE Keys
 - Easy Leveling
 - Draft Ring
 - AZSM
 - IZSM

Specifications:

COUNTING FEATURE SPECIFICATIONS

Database Capacity 6 GB (Available) - Preloaded w/ National Drug Code Directory
MW (Minimum Piece Weight) 30mg (3e)
MSS (Minimum Sample Size) 20 pieces
Sample Size Selection 10, 30, 60, 90, 100

UNIT SPECIFICATIONS

Maximum Capacity 500g
Readability (d) 0.001g
Verification Unit (e) 0.01g

Stabilization time (typical)	Approx. 3s
Calibration	Internal and Automatic
Tare Range	-500g
Accuracy Class	II
Pan Dimension	120mm
Scale Dimensions	216 x 345 x 90 mm
Operating Temperature	+15C to +30C
RS232 Port	Bidirectional - used for Scanner and Printer connections
PS2 Keyboard Port	Standard - compatible with any standard PS2 Keyboard
RJ45 Network Port	Standard - TCP/IP Network Connection
Wi-Fi (500sx /w models)	High Performance "g" Type
Barcode Scanner	High Performance Omni-directional Laser

SERVER SPECIFICATIONS

CPU	500 MHz
RAM Memory	512 MB DDR-SDRAM
Disk Capacity	8 GB
Disk Type	High Performance , premium quality CF card
Ports	4 Ethernet ports (1 Internet and 3 Private Scale Ports)
Port Expansion Card (optional)	4 Ethernet ports
Wi-Fi (Wi-Fi models Only)	"g" Type